

► Package Leak Detectors

Control Unit Plus for LEAK-MASTER® EASY



Made in Germany

Product of



Controller for leak detector LEAK-MASTER® EASY. In combination with LEAK-MASTER® EASY features non-destructive detection of the smallest leaks without the need of costly helium.

Pre-defined measurement programmes, an altitude simulation as well as an user independently quick and continuously working mode characterise this device.



Easily connected to your LEAK-MASTER® EASY.

A flexible controller to guarantee quality and productivity of production processes.

Benefits


- minimal response time
- quick product change
- no calibration required
- simple to operate via touch-screen
- easy installation and start-up
- permanent monitoring of set limit values
- operator friendly – data and process parameter entry and administration by means of integrated keyboard or remote personal computer (e.g. MS-Excel®)
- perfect documentation by complete user- and product data as well as error logs
- remote transmission of results via Ethernet
- Ethernet connection for network integration
- measured data storage
- administration of product names
- user management for measurement personalization
- individual configurable error codes with identification from type and location of leak
- ideal for altitude simulation testing

- for retrofitting your existing LEAK-MASTER® EASY
- hygienic and easy to clean splash-proof stainless steel cabinet / housing

Options

- Barcode Reader for simple and quick user/product selection with IP-protection

Other models, options and accessories available on request.



Type	Control Unit PLUS for LEAK-MASTER® EASY
Vacuum	max. 800 mbar
Temperature (gas/environment)	0 °C up to +40 °C
Interfaces	Ethernet (optional WLAN) RS 232 with ASCII-output of date, time, measured value RJ45 Ethernet FTP-Server for profiles, product and user data, software Update analog output 4-20 mA or 0-10 V
Housing	stainless steel, IP 43
Weight	approx. 8 kg
Dimensions (HxWxD) with carry handle	approx. 110 x 300 x 260 mm
Voltage	100 – 240 V AC; 50 – 60 Hz
Power consumption	230 V AC / 0.12 A
Approvals	Company certified according to ISO 9001 and ISO 22000 CE marked according to: - EMC 2014/30/EU - Low Voltage Directive 2014/35/EU for food-grade gases according to: - Regulation (EC) No 1935/2004

Middle East

Regus Nassima Tower, 4th & 5th Floor Sheikh Zayed
Road, Trade Centre District Dubai, UAE 124303

Phone: +971 4311 6197



Gas Control Equipment

- Gas Mixing Systems
- Gas Metering Systems
- Gas Analysers
- Gas Pressure Vessels
- Engineering Of Customised Systems

Asia Pacific

Level 16, The Pavilion Tower, Jalan Raja Chulan,
50200, Kuala Lumpur, Malaysia

Phone: +603 2182 9754-5

Fax: +603-2182 9797



Gas Safety Equipment

- Flashback Arrestors
- Non-return Valves
- Quick Couplings
- Safety Valves
- Stainless Steel Devices
- Gas Filters
- Pressure Regulators
- Lance Holders
- Ball Valves
- Automatic Hose Reels
- Test Equipment
- Accessories
- Customised Safety Devices

Europe

Florianstr. 15-21, 44139 Dortmund, Germany

Int'l: +1(213) 457 - 3147

Tel: +49 2302 663 4646

Tel: +49 231 292 96 5056



M.A.P Equipment

- Gas Mixing Systems
- Gas Analyzers
- Leak Detection Systems
- Modified Atmosphere Packaging Solution

letstalk@vivangas.com

www.vivangas.com