

▶ **LEAK DETECTION SYSTEM**

LEAK-MASTER® PRO



Made in Germany

Product of



Leak detection for large packages or boxes, based on CO₂-technology. LEAK-MASTER® PRO features non-destructive detection of the smallest leaks without the need for costly Helium.

Benefits

- minimal response time
- quick product change
- for flexible and rigid packs
- no calibration required
- operator friendly – data and process parameter entry by means of integrated keyboard or remote personal computer (e.g. MS-Excel®)
- easy-to-use intuitive system – no special skills required
- convenient data administration and evaluation for customer oriented quality documentation
- two chamber sizes (HxWxD) 140 x 680 x 500
230 x 680 x 500
- easy installation and start-up
- easy to clean splash-proof stainless steel cabinet / housing
- remote transmission of results via Ethernet
- potential free alarm contact for connection of external audible/visual device




Options


- Barcode Reader with IP-protection for simple and quick user/product selection
- wireless data transmission via WLAN (WIFI)



Type	LEAK-MASTER® PRO	Alarms	potential free contact max. 250 V AC or 24 V DC/2 A
Measuring System	infrared measuring cell for CO ₂	Interfaces	Ethernet (WLAN optional)
Measuring range	0 ppm - 5 000 ppm	Cabinet / Housing	stainless steel, IP 54 (splash-proof)
Resolution	1 ppm	Approvals	Company certified according to ISO 9001 and ISO 22000 CE marked according to: - EMC 2014/30/EU - Low Voltage Directive 2014/35/EU - Machinery safety 2006/42/EC for food-grade gases according to: - Regulation (EC) No 1935/2004
Warm-up time	approx. 10 min.		
Calibration	not required		
Response time of the sensor	approx. 1 sec.		
Leak testing cycle	Leak testing cycle		
Vacuum	depends on leak size, CO ₂ -percentage in package, size of chamber		



Two chamber sizes – 100%-analysis especially for large packages or boxes, e.g. E2.

Model	Chamber-size approx. in [mm] (inch) (H x W x D)	Cabinet / housing-size approx. in [mm] (inch) (H x W x D)	Weight approx. [kg]	Pump capacity [kWh]	Pump suction capacity [m ³ /h]	Voltage	
	LM 12.1	230 x 680 x 500 (9.1 x 26.8 x 19.7)	1 025 x 760 x 855 (40.4 x 29.9 x 33.7)	225	2.20	100	400 V AC
	LM 12.2	140 x 680 x 500 (5.5 x 26.8 x 19.7)	1 025 x 760 x 855 (40.4 x 29.9 x 33.7)	225	1.50	63	400 V AC

Caution!

This equipment is not suitable for the checking of packaging featuring O₂ content greater than 20.9% (fresh meat, for example).

Middle East

Regus Nassima Tower, 4th & 5th Floor Sheikh Zayed
Road, Trade Centre District Dubai, UAE 124303

Phone: +971 4311 6197



Gas Control Equipment

- Gas Mixing Systems
- Gas Metering Systems
- Gas Analysers
- Gas Pressure Vessels
- Engineering Of Customised Systems

Asia Pacific

Level 16, The Pavilion Tower, Jalan Raja Chulan,
50200, Kuala Lumpur, Malaysia

Phone: +603 2182 9754-5

Fax: +603-2182 9797



Gas Safety Equipment

- Flashback Arrestors
- Non-return Valves
- Quick Couplings
- Safety Valves
- Stainless Steel Devices
- Gas Filters
- Pressure Regulators
- Lance Holders
- Ball Valves
- Automatic Hose Reels
- Test Equipment
- Accessories
- Customised Safety Devices

Europe

Florianstr. 15-21, 44139 Dortmund, Germany

Int'l: +1(213) 457 - 3147

Tel: +49 2302 663 4646

Tel: +49 231 292 96 5056



M.A.P Equipment

- Gas Mixing Systems
- Gas Analyzers
- Leak Detection Systems
- Modified Atmosphere Packaging Solution

letstalk@vivangas.com

www.vivangas.com