





KM ...-2 KM ...-3

Gas mixing systems for 2 or 3 defined gases, designed for a variety of industrial applications for example, welding applications.

Capacity range up to approx. 350 NI/min. For the exact pressure and flow capacity ratios, please see the technical data overleaf.

Easy operation

- a proportional mixing valve (-2) or three single mixing valves (-3), each with a control knob and %-scale, provide infinitely variable mixture settings
- infinitely variable flow setting with scaled control knob

High process reliability

- independent of pressure fluctuations in the gas supply
- independent of withdrawal fluctuations (in permitted range)
- robust stainless steel housing

Other models, options and accessories available upon request.

Please identify the individual gases at the time of enquiring!

GAS MIXER KM 20/30/60/100



Type KM 20/30/60/100-2; KM 20/30/60/100-3

Gases all technical gases (excluding toxic and corrosive gases

also mixtures of fuel gas with air, O2 or N2O)

Mixing range 0 - 25% (KM 60/100 only) or 0 - 100%

by selection of suitable mixing range the accuracy corresponds to ISO 14175

Pressure settings see tables

Inlet pressure differential

between the gases max. 3 bar
Mixture output (air) see tables

min. mixture output = 1/5 of the max. mixture output

Note!

Flow < 8 NI/min not possible!

Setting accuracy $\pm 1\%$ abs. (scale 0 - 25%), $\pm 2\%$ abs. (scale 0 - 100%)

Mixing precision better than ±1% abs.

Gas connections KM 20/30/60 G 1/4 RH with cone, hose nipple 6 mm
Gas connections KM 100 G 3/8 RH with cone, hose nipple 8 mm

For fuel gases:

fuel gas connection

and outlet at mixer G 3/8 LH with cone, soldering nipple for pipe OD 10 mm

Housing stainless steel

Weight approx. 12 kg (-2), approx. 21 kg (-3)

Dimensions (HxWxD) approx. 250 x 165 x 340 mm (9.84 x 6.50 x 13.39 inches)

(-2 without connections)

approx. 250 x 370 x 340 mm (9.84 x 14.57 x 13.39 inches)

(-3 without connections)

Approvals Company certified according to ISO 9001

CE-marked according to:

- ATEX 114 Directive 2014/34/EU

Flow KM 20 (in NI/min) in relation to air														
	outlet pressure in barg													
		0.5	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	
	2	8	-	-	-				No	te:				
	3	-	10	-	-	R	educe	ed mi	xture	outpu	ıt in c	ase o	f	
	4 13 - higher outlet pressures.													
min. inlet	5	-	-	-	17	-	-	-	-	-	-	-	-	
pressure	6	-	-	-	-	20	-	-	-	-	-	-	-	
in barg		-	-	-	-	-	24	-	-	-	-	-	-	
(max.	8	-	-	-	-	-	-	27	-	-	-	-	-	
13 bar)		-	-	-	-	-	-	-	30	-	-	-	-	
	10	-	-	-	-	-	-	-	-	34	-	-	-	
	11	-	-	-	-	-	-	-	-	-	37	-	-	
	12	-	-	-	-	-	-	-	-	-	-	40	-	
	13	-	-	-	-	-	-	-	-	-	-	-	44	

	13												44	
Flow KM 60 (in NI/min) in relation to air														
outlet pressure in barg														
		0.5	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	
	2	24	-	-	-				Not	e:				
	3	-	39	-	-	R	educ	ed mi	xture	outpu	ıt in c	ase o	f	
		-	-	53	-	higher outlet pressures.								
min. inlet		-	-	-	68	-	-	-	-	-	-	-	-	
pressure		-	-	-	-	82	-	-	-	-	-	-	-	
in barg		-	-	-	-	-	96	-	-	-	-	-	-	
(max.		-	-	-	-	-	-	109	-	-	-	-	-	
13 bar)		-	-	-	-	-	-	-	123	-	-	-	-	
	10	-	-	-	-	-	-	-	-	137	-	-	-	
	11	-	-	-	-	-	-	-	-	-	151	-	-	
	12	_	_	_	_	_	_	_	-	_	_	165	- 1	

JII COLIVO Z	711 COLIVE 20 14/04/LO													
Flow KM 30 (in NI/min) in relation to air														
outlet pressure in barg														
		0.5	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	
	2	13	-	-	-				Not					
	3	-	21	-	-	Re	educe	ed mix			ıt in c	ase o	f	
		-	-	29	-		hi	gher	outlet	pres	sures		ı	
min. inlet		-	-	-	36	-	-	-	-	-	-	-	-	
pressure		-	-	-	-	44	-	-	-	-	-	-	-	
in barg		-	-	-	-	-	51	-	-	-	-	-	-	
(max.		-	-	-	-	-	-	59	-	-	-	-	-	
13 bar)		-	-	-	-	-	-	-	66	-	-	-	-	
	10	-	-	-	-	-	-	-	-	73	-	-	-	
	11	-	-	-	-	-	-	-	-	-	81	-	-	
	12	-	-	-	-	-	-	-	-	-	-	88	-	
	13	-	-	-	-	-	-	-	-	-	-	-	95	

Flow KM 100 (in NI/min) in relation to air														
outlet pressure in barg														
		0.5	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	
	2	47	-	-	-				Not	e:				
	3	-	77	-	-	Re	educe	ed mi	xture	outpu	ıt in c	ase o	f	
	4	-	-	105	-		hi	gher	outlet	pres	sures			
min. inlet	5	-	-	-	133	-	-	-	-	-	-	-	-	
pressure		-	-	-	-	160	-	-	-	-	-	-	-	
in barg		-	-	-	-	-	188	-	-	-	-	-	-	
(max.		-	-	-	-	-	-	215	-	-	-	-	-	
13 bar)		-	-	-	-	-	-	-	242	-	-	-	-	
	10	-	-	-	-	-	-	-	-	269	-	-	-	
	11	-	-	-	-	-	-	-	-	-	296	-	-	
	12	-	-	-	-	-	-	-	-	-	-	323	-	
	13	-			-	-	-	-	-	-	-	-	350	